
## **Mini-Mover Conveyors**

## Specsheet 40202

LP Series Conveyors With T-Slot Profile Removed -- Available Tapped Holes



Idler End

Notes: 1) All values are inches 2) All dimensions are from the 0-0 Point 3) All holes tapped 10-32 with 82° x 0.31" Ø C-sink

4) Depending on the drive mounting style, some holes may not be available

Length Model	А	В	С	D	Е	F	G	Н	- 1	J	K	L	М	N	0	Р	Q	R	S	Т	U	V
18 "X"	3.165	4.415	8.187	13.209	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A										
"Y"	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A										
24 "X"	3.165	4.415	8.665	19.665	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A										
"Y"	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A										
30 "X"	3.165	4.415	10.455	17.745	25.035	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A									
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A									
36 "X"	3.165	4.415	10,290	17.415	24.540	31,665	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A								
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A							
42 "X"	3.165	4.415	9.985	16.805	23.625	30.445	37.265	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A							
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A							
48 "X"	3.165	7.050	9.915	16.665	23.415	30.165	36.915	43.665	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A						
"Y"	-0.435	-0.435	-0435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A						
60 "X"	3.165	4.415	10.585	18.005	25.425	32.845	40.265	47.685	55.105	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
72 "X"	3.165	4.415	10.242	17.319	24.396	31.473	38.550	45.627	52.704	59.781	66.858	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
84 "X"	3.165	4.415	11.593	20.021	28.449	36.877	45.305	53.733	62.161	70.589	79.017	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0.435	0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
96 "X"	3.165	4.415	11.159	19.153	27,147	35.141	43.135	51.129	59.123	67.117	75.111	83.105	91.099	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
108 "X"	3.165	4.415	10.859	18.553	26.247	33.941	41.635	49.329	57.023	64.717	72.411	80.105	87.799	95.493	103.187	N/A						
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A						
120 "X"	3.165	4.415	10.639	18.113	25.587	33.061	40.535	48.009	55.483	62.957	70.431	77.905	85.379	92.853	100.327	107.801	115.275	N/A	N/A	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A	N/A	N/A
132 "X"	3.165	4.415	10.469	17.773	25.077	32.381	39.685	46.989	54.293	61.597	68.901	76.205	83.509	90.813	98.117	105.421	112.725	120.029	127.333	N/A	N/A	N/A
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	N/A	N/A	N/A
144 "X"	3.165	4.415	9.973	16.781	23.589	30.397	37.205	44.013	50.821	57.629	64.437	71.245	78.053	84.861	91.669	98.477	105.285	112.093	118.901	125.709	132.517	139.325
"Y"	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435	-0.435