

Mini-Mover

	MODEL	STANDARD TABLE FEATURES				STANDARD CONVEYOR FEATURES	
UniMate [®]							
The Uni-Mate® is a portable and economical bundling of rotary table accumulator and conveyor — ideal for unattended and overnig lights-out operation. For manufacturing facilities with multiple shifts or varied machine-cell setups throughout the factory, the higl adjustable Uni-Mate® is easy to transport, configure and operate.	-	24" diameter PVC top 10.5" - 34" height adjustment range Gearmotor 1/12 hp, 60W BLDC 1-3 RPM variable-speed rotation Cycle /index timer Locking steel casters Diverter arm & cushion 19.5" square steel base Load capacity: 65 lbs Unit weight: 95 lbs			сĭ	Choice of 4 conveyor dimensions: 4" x 36" (approx. wt. 15 lbs.) 6" x 36" (approx. wt. 20 lbs.) 4" x 48" (approx. wt. 20 lbs.) 6" x 48" (approx. wt. 25 lbs.) 2.50" high conveyor frame with integral 0.70" high side guides	
	80-032	32" diameter PVC top 10.5" - 42" height adjustment range Gearmotor 1/12 hp, 60W BLDC 1-3 RPM variable-speed rotation Cycle /index timer Locking steel casters Diverter arm & cushion 19.5" square steel base Load capacity: 100 lbs				Integral left-side mount gearmotor, 1/18 hp, 115/60 VAC 3 fpm fixed speed Belt can stop-start in synch with table on a single cycle timer	
		48" diameter PVC top 10.5" - 36" height adjustment range			1.25" dia. pulleys, crowned		
	80-048				aluminum with double-sealed long-life bearings Blue chemical & cut resistant belt with H0 (0.16" high) cleats, 6" spacing		
Model 80-024 Shown with 4"x conveyor	6"	Gearmotor 1/12 hp, 60W BLDC 1-3 RPM variable-speed rotation Cycle /index timer Locking steel casters Diverter arm & cushion					
		19.5" square steel base Load capacity: 100 lbs Unit weight: 145 lbs			Up to 45-degree adjustment range on connection to rotary table		
		80-24	80-32	80-48	Uni	-Mate™ Options	
		•	•	•	1	nveyor Drip Pan	
		• Table Drip		le Drip Pan			
		٠	•	•	IP-6	-65 gearmotors	
		•	•	•	U2 9	Sealed Belting (flat or cleated)	
		•	•	•		able Base Extenders able Overhead Paddle System able Stainless Steel Overlay	
		•	•	•			
		•	•	•			
		•	•	•	Tab	le Stationary Fence	
Nodel 80-032 Shown with 6" x 36" conve and Overhead Double Pace		Note Not Not </td					

* Note: Mini-Mover conveyors reserves the right to change / discontinue features or specifications without notice